



COMMANDER

- Standard and SMART Analogue and IP options available
- Vandal Resistant Handset and Cord
- Robust and weather resistant: IP65
- Full keypad, full keypad with memory, CB and 1, 3 and 6 button programmable autodialler telephones
- Dual purpose design for wall or desk mounting, simple installation
- Large tactile buttons, easy to see and operate
- Inductive Coupler fitted as standard for hard of hearing
- Standard or Customised units
- CE Compliant



TITAN

- Standard and SMART Analogue and IP options available
- Vandal Resistant Handset and Cord
- Robust and weather resistant: IP54 to IP66
- Full keypad, full keypad with memory, CB and 1, 3 and 6 button programmable autodialler telephones
- Multi purpose design for wall or post mounting, simple installation
- Large tactile buttons, easy to see and operate
- Inductive Coupler fitted as standard for hard of hearing
- Standard or customised units
- CE Compliant



VR

- Standard and SMART Analogue and IP options available
- Vandal Resistant Metal Buttons
- Hands free operation (VOX)
- Robust and weather resistant: Up to IP65
- 1, 2 or 3 button autodial options with remote programming
- Dual purpose design for flush or surface mounting, simple installation
- Optional Induction Loop facility for hearing impaired
- Line powered down to 25mA
- Optional mains supply adapter
- Non-volatile memory store
- Audio-visual ring indication
- CE Compliant



SENTINEL

- Full keypad with remote programming
- DTMF/LD dialling
- Line powered down to 25mA
- Optional mains supply adapter
- Hands free operation (VOX)
- Non-volatile memory store
- Audio-visual ring indication
- Flush or surface mounting
- Volume adjust on installation and on front panel
- CE compliant (SMART option tested to CTR 21)
- Optional variant available with SMART (Self Monitoring And Reporting)



HYGEIA

- Full key pad
- Flat membrane fascia, resists contamination
- Hands free operation (VOX)
- DTMF/LD dialling
- Audio-visual ring indication
- REN 1
- CE Compliant
- Flush or surface mounting
- Volume adjust on installation and on front panel
- Power Supply included



AUTELDAC 4

- Ex II 2 G ATEX certified telephone
- CE (R&TTE Directive 1999/5/EC and ATEX Product Directive 94/9/EC)
- IEC Ex certified
- Fully compliant with TBR21 / TBR38
- Full keypad with 3 programmable memory buttons, or CB variant
- Headset Option
- 90dB sounder (adjustable)
- Secondary beacon / external sounder actuator
- Robust and weather resistant up to IP66
- Industry standard robust handset c/w curly cord or armoured stainless steel.
- Noise cancelling versions available

Self Monitoring And Reporting Telephone

Software driven remote maintenance

S.M.A.R.T.

- Automatic fault reporting
- Silent interrogation
- Standard 2 wire connection
- Remote autodialler re-programming
- Telephone fault database
- Remote maintenance
- Call Logging

DAC Telephony

Telephone Features

Features Comparison Chart

	Commander	Titan	VR	Sentinel	Hygeia	Auteldac 4
Description	Weather and vandal resistant	Weather and vandal resistant	Weather and vandal resistant	Weather and vandal resistant	Sterile area	Hazardous area ATEX approved
S.M.A.R.T. Options	Yes	Yes	Yes	Yes	No	No
Casing Material	Glass filled polyester	Die cast aluminium, epoxy powder coated	Aluminium sheet, polyester powder coat finish	Aluminium sheet, polyester powder coat finish	Aluminium sheet with impermeable multi-layer chemically inert polyester	Carbon loaded glass-filled polyester (colour: black)
CE Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Dialling System	DTMF/LD & ELR/TBR	DTMF/LD & ELR/TBR	DTMF/LD & ELR/TBR	DTMF/LD & ELR/TBR	DTMF/LD & ELR/TBR	DTMF/LD & ELR/TBR
Flush-Mount Option	No	Yes	Yes	Yes	Yes	No
Handset Cord	Armoured & Curled	Armoured & Curled	N/A	N/A	N/A	Armoured & Curled
IP Rating	IP65	up to IP66	up to IP65	up to IP65	up to IP65	Up to IP66
Operating Temperatures	-20° to +55°C	-20° to +60°C	-20° to +60°C	-20° to +60°C	-20° to +55°C	-20° to +50°C
Power Supply	Telephone line	Telephone line	Telephone line optional mains supply adaptor	Telephone line optional mains supply adaptor	Telephone line mains supply adaptor included	Telephone line
Relative Humidity	to 95% non-condensing	to 95% non-condensing	to 95% non-condensing	to 95% non-condensing	to 95% non-condensing	to 95% non-condensing
Ringling Tone	Shrill warble, 80dBA	Dual, 80dBA	Dual, 75dBA	Dual, 75dBA	Dual, 75dBA	Shrill warble >90dBA
Dimensions W x H x D (vertical mounting)	190 X 292 X 140mm	189 x 366 x 130mm (with door)	181 x 352 x 48mm 189x366x60 w b/box	181 x 352 x 48mm 189x366x60 w b/box	181 X 352 X 48mm	190 x 292 x 140mm
Weight	Approx. 3kg	up to 5kg	Approx. 1.2kg (3kg with backbox)	Approx. 1.1kg (3kg with backbox)	1.1kg	3.1kg



GAI-Tronics, UK - Tel: +44 (0)1283 500500 - Fax: +44 (0)1283 500400 - www.gai-tronics.co.uk
 GAI-Tronics Corporation, USA - Tel: +1(610) 777 1374 - Toll Free: 800 492 1212 - Fax: +1(610) 775 6540 - www.gai-tronics.com
 GAI-Tronics S.r.l, Italy - Tel: +39 02 48601 460 - Fax: +39 02 4585 625
 GAI-Tronics Corporation, Malaysia - Tel: +60 3 8945 4035 - Fax: +60 3 8945 4675
 An ISO9001 Registered Company
 The policy of GAI-Tronics is one of continuous improvement, therefore the company reserves the right to change specifications without notice.